


* 19" X 36" SERVICE OPENING

DUPLEX POWER CONNECTION POINT INSIDE OF HEADER
 PRESENCE SENSOR
 BOTH SIDE FRAMES ARE HOLLOW FOR ELECTRICAL ACCESS FROM EACH CORNER LEADING TO THE HEADER.



ELECTRICAL REQUIREMENTS
 USA (DOMESTIC) : 115 vac - 60 HZ WITH A 15 amp BRANCH CIRCUIT
 INTERNATIONAL : 220/240 vac - 50/60 HZ WITH A MAX. 8 amp BRANCH CIRCUIT

UNIT SPECIFICATIONS:
 104/120 VOLTS
 3 ACTUAL UNIT AMPS
 60 HZ

275 - 43-1/2" H GLAZING ROUGH OPENING = 43-3/4" H (1111 mm)
 47-3/4" W (1213 mm) MASONRY ROUGH OPENING = 48" W (1219 mm) x 44" H (1118 mm)
 47-1/2" W X 35-3/4" H GLAZING ROUGH OPENING = 47-3/4" W (1213 mm) x 36" H (914 mm)
 MASONRY ROUGH OPENING = 48" W (1219 mm) x 36-1/4" H (921 mm)

* TWO STANDARD WINDOW HEIGHTS

43-1/2" H WITH 19"W x 36"H SERVICE OPENING
 35-3/4" H WITH 19"W x 28"H SERVICE OPENING